



Taxi Top

LED Screen Series

O1 / Double Side High Resolution Advertising Series

02 / Double Side Thick Series

03 / Double Side Triangle Series

04 / Single Side Simple Advertising Series



SPECIFICA [*]	TION			
Item	Model	P2.5	P3.3	P5.0
Pixel pitch	Unit	2.5	3.3	5.0
LED type	N/A		SMD 3 in 1	
Pixel density	Pixels/m²	160000	90000	40000
Cabinet size(WxHxT)	mm		1106x408x141	
Materia	N/A		Aluminum	
Display size	mm		960x320	
Resolution	Pixels	384x128	288x96	192x64
Control way	N/A		WIFI/4G	
Input voltage	V		DC8~18	
Screen weight	Kg/pc		15~17	
Brightness	Nits		4500~5000	
Refresh rate	Hz		5120	
Ingress protection	N/A		IP65	
Max. Avg. Power consumption	W/m²		480/160	



SPECIFICATION						
Item	Model	P2.0	P2.5	P3.3	P4.0	P5.0
Pixel pitch	Unit	2.0	2.5	3.3	4.0	5.0
LED type	N/A			SMD 3 in 1		
Pixel density	Pixels/mt	250000	160000	90000	62500	40000
Cabinet size(WxHxT)	mm			1106x386x139		
Materia	N/A			Aluminum		
Display size	mm			960x320		
Resolution	Pixels	480x160	320x160	288x96	240x80	240x80
Control way	N/A			WIFI/4G		
Input voltage	V			DC8~20		
Screen weight	Kg/pc			16~17		
Brightness	Nits			4500~5000		
Refresh rate	Hz			3840		
Ingress protection	N/A			IP65		
Max. Avg. Power consumption	W/m²			450/150		



SPECIFICATION						
Item	Model	P1.87	P2.5	P3.076	P4.0	P5.0
Pixel pitch	Unit	1.87	2.5	3.076	4.0	5.0
LED type	N/A			SMD 3 in 1		
Pixel density	Pixels/mt	284444	160000	105685	62500	40000
Cabinet size(WxHxT)	mm			990x395x135		
Materia	N/A			Steel		
Display size	mm			960x320		
Resolution	Pixels	480x180	384x128	312x104	240x80	192x64
Control way	N/A			WIFI/4G		
Input voltage	V			DC8~20		
Screen weight	Kg/pc			17~19		
Brightness	Nits			4500~5000		
Refresh rate	Hz			1920		
Ingress protection	N/A			IP65		
Max. Avg. Power consumption	W/m²			550/165		



SPECIFICA	TION			
Item	Model	P2.5	P3.3	P4.0
Pixel pitch	Unit	2.5	3.3	4.0
LED type	N/A		SMD 3 in 1	
Pixel density	Pixels/mt	160000	90000	62500
Cabinet size(WxHxT)	mm		810x150x175	
Materia	N/A		ABS plastic	
Display size	mm		800x160	
Resolution	Pixels	320x64	240x48	200x40
Control way	N/A		WIFI/4G	
Input voltage	V		DC8~18	
Screen weight	Kg/pc		6	
Brightness	Nits		4500~5000	
Refresh rate	Hz		1920	
Ingress protection	N/A		IP65	
ax. Avg. Power consumption	W/m²		120/40	



LED Screen Manufacturer in China





Mob: +86 153 9990 6913 Web: www.bibiled.com E-mail: info@bibiled.com

Address:

The Third Floor, Jiada Industrial Park, Shiyan Town, Baoan District, Shenzhen, China.